



OPEN GEAR LUBRICANT (STANDARD)

Spanjaard Open Gear Lubricant (Std) is a black, tacky, heavy duty, bentone-based lubricant containing oxidation, corrosion, molybdenum disulphide and other extreme pressure additives.

APPLICATIONS

Spanjaard Open Gear Lubricant (Std) is a lower-cost open gear lubricant for all medium to fast-moving open or exposed gears, as found on cranes, excavating plant and winches, suitable for adverse weather conditions or in a contaminated atmosphere e.g. cement works, paper mills, steel mills, drilling rig jacking legs, at sea etc.

TYPICAL PROPERTIES

Colour	Black
Consistency - NLGI Grade	2
Worked penetration, 1/10mm	265-295
Flash Point COC, °C	285
Base on viscosity	
cSt @ 40°C	550
cSt @ 100°C	36
Operating temperature	
Continuous service, °C	-10 to 140
Short period peaks, °C	200



CP/su/ Open Gear Lubricant(Standard) – July 2014

HANDLING AND STORAGE

Store under cover with lid closed.
Keep out of reach of children.
If swallowed, seek medical help. Do not induce vomiting.

PACKAGING

500g, 5kg, 15kg, 50kg, 180kg

**Certified as an
ISO 9001
Manufacturer by the
SABS**

**Developers, Manufacturers
& Distributors of
Specialised
Lubricants & Allied
Chemical Products**

P.O. BOX 21
HUNTINGDON
CAMBS PE29 2ED
ENGLAND
TEL: +44 1480 45-7022
FAX: +44 1480 45-7022
WEBSITE: www.spanjaard.biz

P.O. BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 11 386-7100
FAX: +27 11 786-5685
EMAIL: sales@spanjaard.biz